

AC/DC[®]UPS

www.acdc.com.tr



Rolling Shutter UPS



- 2 Year Warranty
- Led and Audial Alerts
- 10 Year Spare Parts Warranty
- 100 -200 Hours of Stand By Time
- Up to 42 Commands Available to Define
- No Usage of Reductor Motor Increases it's Safety
- Shutter and UPS Control Via One Remote Control
- Easy to Install Thanks to it's Small and Elegant Design
- Operates In Hi and Low Voltage (150 VAC - 270 VAC)
- Monitors 4 Different Shutters With it's 4 Smart Remote Controls

AC/DC[®] Rolling Shutter UPS

AC/DC Rolling Shutter UPS are uniquely designed UPS systems to make all sort of motors work without interruption. The most essential advantage is their 100-200 hours of stand-by period. They can be used in any work place with a motorized shutter or window brackets, garage doors, automatic door system or any place with a tube shaped motor. They can be fixed to the wall thanks to their smart type structures. The usage and the montage are easy. The most significant difference to other UPS systems is their long stand-by time during electricity break and their 2 smart remote controls.

TECHNICAL SPECIFICATIONS

	R-GK750	R-GK1500
Power	750 W (1000 VA)	1500 W (2000 VA)
Input Voltage	220 VAC ; 1 Phase	220 VAC ; 1 Phase
Input Frequency	50/60 Hz	50/60 Hz
Output Voltage	220 VAC ; 1 Phase	220 VAC ; 1 Phase
Output Frequency	50/60 Hz	50/60 Hz
Line Operation Range	150-270 VAC	150-270 VAC
Rf Operating Frequency	433,92 MHz	433,92 MHz
Battery Type	No Maintenance Dry Type Battery	
Battery No	2 pcs of 12 V 7 Ah	4 pcs of 12 V 7 Ah
Battery Lifespan	5 Year	5 Year
Charge Time	12 Hours	12 hours
Stand-By Time	4 Day (100 hours)	8 Day (200 hours)
Remote Control Distance	30 mt	30 mt
Displays	Network Voltage and Inverter Voltage Leds	
Alarm and Warnings	Battery Working Alert	
Protections	Overload Protection	
Operating Temperature	0 °C ~ 40 °C	0 °C ~ 40 °C
Net Weight	12 kg	12 kg
Lifting Weight	190 kg	400 kg
Dimensions	335 x 190 x 120 mm	335 x 265 x 120 mm
Options	External Receiver Unit, Max. 42 Extra Commands	

